

BALLISTIC SHIELDS

Data sheet TenCate Targa-Light™ CX-400 TL /K-OPS 500

ADVANCED ARMOUR

CX-400 TL /K-OPS 500

Configuration	Anti-ballistic shield NIJ 0108.01, Level III
Type of protective cover	Black textile or TenCate Rosist®
Product application	Anti-ballistic shields with wheeled chassis.

SPECIAL THREATS TESTED

7.62 x 39 AK 47 MSC	
7.62 x 51 M80	
The above list of ammunition is not exhaustive and may not include threats that can be defeated by this product	



SPECIFICATIONS

Rifle ammo resistant	Multi-hit capability	Stop in plate capability	Lightweight
7.62 x 39 AK 47 MSC NIJ 0108.01, Level III	6 shots NIJ 0108.01, Level III	Against listed threats	54 +/- 3kg assembled*
Dimensions	Shape	Composition	Durable
1950x500mm**	Rectangular, flat or single curved	HPPE	Sealed edges
*) Lower shield: 12.5 kg ± 1 kg, Upper shield: 17.5 kg ± 1 kg **) Lower shield : 500x1000mm, Upper shield : 500x1000mm			

AVAILABLE OPTIONS (Details on request)

- › Additional ballistic plate NIJ level IV
- › Transport bag
- › Camera (D/N, IR)
- › Lamp (LED, IR, Laser)

MAIN CHARACTERISTIC

- › Composed of 2 ballistic shields & 1 chassis
- › Assembly/disassembly of the complete shield on chassis is tool-free
- › Adjustable height from 1650 mm to 1950 mm
- › Chassis with 4 rotating wheels 360°
- › Brake on the rear wheels
- › Additional ballistic plate NIJ III + MSC to protect feet (during stand-by phase)

HANDLING

Keep away from intense heat source

- › Do not drop the shield on the floor and avoid hard shocks
- › Do a visual inspection of the shield every six-months
- › In case of visual damage, send the shield back for inspection / repair
- › Only clean with pure water and mild soap
- › Use only as a shield, do not sit or walk on it

GUARANTEE PERIOD

The shield is expected to preserve its conformity with the specifications for a period of at least 5 years during storage from the date of delivery, provided that:

- › The product is stored under dry conditions at normal ambient temperature
- › The product has not been subjected to peak temperature exceeding 70°C
- › The product is protected against long term direct exposure to sunlight